Package 'matrixcut'

March 24, 2023

Version 0.0.1

Date 2023-03-19

Title Determines Clustering Threshold Based on Similarity Values

Maintainer Matthew Cserhati <csmatyi@protonmail.com>

Description The user must supply a matrix filled with similarity values. The soft-

ware will search for significant differences between similarity values at different hierarchical levels. The algorithm will return a Loess-smoothed plot of the similarity values along with the inflection point, if there are any. There is the option to search for an inflection point within a specified range. The package also has a function that will return the matrix components at a specified cutoff. References: Mullner. <ArXiv:1109.2378>; Cserhati, Carter. (2020, Journal of Creation 34(3):41-

50), <https://dl0.creation.com/articles/p137/c13759/j34-3_64-73.pdf>.

License GPL (>= 3) Encoding UTF-8 LazyData true RoxygenNote 7.2.3 Imports igraph, stats, inflection

NeedsCompilation no

Author Matthew Cserhati [aut, cre] (<https://orcid.org/0000-0002-3673-9152>)

Depends R (>= 3.5.0)

Repository CRAN

Date/Publication 2023-03-24 16:30:02 UTC

R topics documented:

matrixcut primates .																			
xenarthra																			

Index

componentplot

Draws a Plot Showing the Number of Components as a Function of the Cutoff Value.

Description

The function takes a square sequence similarity matrix and calculates the number of independent components in which the sequence similarity between the members is greater than a specified value (between 0 and 1). It creates a plots showing the number of components corresponding to a given cutoff value. The function also depicts the inflection point with a vertical line. Upper and lower bounds can be provided between which the inflection point will be found (if it exists).

Version 0.0.1. Author: Dr. Matthew Cserhati Email: csmatyi@protonmail.com March 19, 2023

Arguments

mx	a square sequence similarity matrix
lower_bound	lower bounds for calculating the inflection point in, default = 0
upper_bound	upper bounds for calculating the inflection point in, default = 1

Value

A plot showing the number of components as a function of the cutoff threshold.

References

Mullner. <ArXiv:1109.2378>

Cserhati, Carter. (2020, Journal of Creation 34(3):41-50), <https://dl0.creation.com/articles/p137/c13759/j34-3_64-73.pdf>

Examples

```
componentplot(xenarthra,0.75,0.9)
componentplot(xenarthra)
```

cutoffplot

Draws a Plot Showing the Number of Similarity Values as a Function of the Cutoff Value.

Description

The function takes a square sequence similarity matrix and creates a plot showing the number of similarity values above a given cutoff value, drawn on the x-axis, ranging from 0 to 1. The function also depicts the inflection point with a vertical line. Upper and lower bounds can be provided between which the inflection point will be found (if it exists).

Version 0.0.1. Author: Dr. Matthew Cserhati Email: csmatyi@protonmail.com March 19, 2023

liliales

Arguments

mx	a square sequence similarity matrix
lower_bound	lower bounds for calculating the inflection point in, default = 0
upper_bound	upper bounds for calculating the inflection point in, default = 1

Value

A plot showing the number of similarity values as a function of the cutoff threshold.

References

Mullner. <ArXiv:1109.2378>

Cserhati, Carter. (2020, Journal of Creation 34(3):41-50), <https://dl0.creation.com/articles/p137/c13759/j34-3_64-73.pdf>

Examples

```
cutoffplot(liliales,0.7,0.85)
cutoffplot(liliales)
```

liliales	Chloroplast	genome	sequence	similarity	matrix	for	163	Liliales
	species							

Description

Chloroplast genome sequence similarity matrix for 163 Liliales species

Usage

liliales

Format

'liliales' Chloroplast genome sequence similarity matrix for 163 Liliales species

matrixcut

Calculates The Component Membership in a Sequence Similarity Matrix at a given Cutoff Value

Description

The function takes a square sequence similarity matrix and calculates those independent components in which the sequence similarity between the members is greater than a specified value (between 0 and 1). The result provied by the function is a list of species with their component membership.

Version 0.0.1. Author: Dr. Matthew Cserhati Email: csmatyi@protonmail.com March 19, 2023

Arguments

mx	a square sequence similarity matrix
cut	a given cutoff value to calculate components for, default value = -1

Value

The inflection point: cutoff value for the optimal number of clusters

A list of the species together with their cluster membership.

References

Mullner. <ArXiv:1109.2378>

Cserhati, Carter. (2020, Journal of Creation 34(3):41-50), <https://dl0.creation.com/articles/p137/c13759/j34-3_64-73.pdf>

Examples

```
matrixcut(primates,0.8)
matrixcut(primates)
```

primates	Mitochondrial	genome	sequence	similarity	matrix	for .	31	primate
	species							

Description

Mitochondrial genome sequence similarity matrix for 31 primate species

Usage

primates

xenarthra

Format

'primates' Mitochondrial genome sequence similarity matrix for 31 primate species

xenarthra	Mitochondrial genome sequence similarity matrix for 37 Xenarthra
	species

Description

Mitochondrial genome sequence similarity matrix for 37 Xenarthra species

Usage

xenarthra

Format

'xenarthra' Mitochondrial genome sequence similarity matrix for 37 Xenarthra species

Index

* datasets liliales, 3 primates, 4 xenarthra, 5 componentplot, 2 cutoffplot, 2 liliales, 3 matrixcut, 4 primates, 4

xenarthra, 5